




DIAMONDDRYERS



P O W E R F U L
E L E G A N T
T O U G H

5 YEAR
WARRANTY

* Limited Warranty

PERFORMANCE



POWERFUL

Low energy - high speed

Fastest drying time with a Carbon free, digital brushless motor

Energy efficient with powerful performance

High intensity single port nozzle



ELEGANT

Stunning design with a high quality Aluminium case, beautiful colours and a diamond cut edge

Blue LED to guide users intuitively to the optimum drying zone

Perfect for washrooms with limited space



**5 YEAR
WARRANTY**

* Limited Warranty




TOUGH

Longest service time with a 5 year warranty

Strong for public areas and high use

Minimal maintenance

COLOUR OPTIONS



SILVER

ROSE GOLD

OBSIDIAN

KEY FEATURES

5 YEAR WARRANTY
*Limited Warranty

COMPACT SIZE

MINIMAL MAINTENANCE

LOW POWER CONSUMPTION

HIGH SPEED DRYING

COMPETITIVE PRICE

UNIQUE MODERN DESIGN WITH A EYE CATCHING ANODIZED FINISH

SPECIFICATIONS



Rated Voltage	AC 220-240 V
Frequency	50/60 Hz
Rated Power	260 W
Standby Power	≤ 0.5 W (satisfied by blueangel regulation)
Sensing Type	Auto infrared touch free operation
Sensing Range	45° 10-20cm
Motor Type	"Brushless DC motor 260 Watts Life time ≥ 5,000 H (1,500,000 operation times based on 12 sec drying time)"
Motor Speed	24,500 RPM
Hand Drying Time	10 - 12 sec
Air Speed	74 m/s (266 km/h)
Effective Airflow	84 m³/h (50 CFM)
LED pointing Light	Blue LED
Noise	≤ 72dB(A) @ 1 meter
Operating Cycle	30 sec (The machine shuts down automatically after 30sec and 2 sec delay turn off form last read)
External Material	Aviation aluminium materials Anodizing, 3mm T, brushed
Protection Device	Protect the main board against over current and over voltage, lightning, over temperature of inside motor, 120 C +/- 5 C and over temperature of main board 85C auto reset safety overload

Anti-theft Function of Machine	2 allen lock screws and lock with allen wrench
Internal Material	Heatproof PP fireproof 94VO
Internal Lead Wire	Temperature resistant 105°C
Method of Connecting Wire	Terminal block
Power Switch	N/A
Dimensions	272 x 136 x 123 mm
Weight	Net: 3.2 kg - Gross 3.8 kg
Approvals	CE, GS, RoHs, IPX2
Protection Rating	IPX2
Electrical Isolation	Class 1
Operating Temperature	-10 - 55°C
Operating Humidity	20-85% RH
Installation Note	Unit can be hard wired by electrician or used with power cord and plug provided (option)
Exterior Screw Type	Two anti-theft lock screws and key wrench
Warranty	5 years warranty ('Limited warranty)
Packing	PE bag, Paper tray, Gift box, Carton



EMAIL US: sales@good-wind.com

GOOD-WIND.COM

g_dwind